

## 40X40X10 mm

## KF0410-01 Series



- **Frame** : Plastic Material UL 94V-0
- **Impeller** : Plastic Material UL 94V-0
- **Speed Range** :  $\pm 10\%$

### SPECIFICATIONS

Model	Bearing	Rated Voltage (V)	Operating Voltage (V)	Air Flow (CFM)	Static Pressure (inchH <sub>2</sub> O)	Speed (R.P.M.)	Input Current (Amp)	Input Power (Watt)	Nominal Power (Watt)	Noise (dBA)	Weight (g)	
KF0410B5H-01	Dual Ball	5	4.25~5.75	6.00	0.128	6000	0.13	0.65	0.8	28.0	14	
KF0410B5M-01				5.38	0.106	5400	0.09	0.45	0.5	25.7		
KF0410B5L-01				4.12	0.066	4200	0.07	0.35	0.4	20.9		
KF0410S5H-01	Sleeve			6.00	0.128	6000	0.20	1.00	1.2	28.0		
KF0410S5M-01				5.38	0.106	5400	0.10	0.50	0.8	25.7		
KF0410S5L-01				4.12	0.066	4200	0.08	0.40	0.6	20.9		
KF0410B1H-01	Dual Ball	12	10.2~13.8	6.00	0.128	6000	0.07	0.84	0.8	28.0		
KF0410B1M-01				5.38	0.106	5400	0.06	0.72	0.7	25.7		
KF0410B1L-01				4.12	0.066	4200	0.05	0.60	0.6	20.9		
KF0410S1H-01	Sleeve			6.00	0.128	6000	0.08	0.96	1.2	28.0		
KF0410S1M-01				5.38	0.106	5400	0.07	0.84	0.8	25.7		
KF0410S1L-01				4.12	0.066	4200	0.06	0.72	0.7	20.9		
KF0410B2S-01	Dual Ball	24	20.4~27.6	6.58	0.148	6600	0.06	1.44	1.4	30.6		
KF0410B2H-01				6.00	0.128	6000	0.05	1.20	1.2	28.0		
KF0410B2M-01				5.38	0.106	5400	0.04	0.96	1.0	25.7		
KF0410B2L-01				4.12	0.066	4200	0.03	0.72	0.8	20.9		
KF0410S2H-01				Sleeve	6.00	0.128	6000	0.05	1.20	1.2		28.0
KF0410S2M-01					5.38	0.106	5400	0.04	0.96	1.0		25.7
KF0410S2L-01	4.12	0.066	4200	0.03	0.72	0.8	20.9					

Specifications subject to change without notice

